

CH0014

Technical Datasheet



Features

- LED status indicator
- Contains charge control module, universal power supply, line cord and cable/connector

Benefits

- Specifically designed to charge Ultralife UBBL09 battery safely and efficiently
- Safety circuit protects against charging shorted packs

Applications

- Commercial desktop charger for UBBL09 battery

| Technical Specifications | |
|--------------------------|---|
| Part No. | CH0014 |
| DC Input | 19-30VDC |
| DC Output | 12.6V |
| Charge Rate | 2.0A |
| Battery Types | Li-Ion |
| User Interface | Off: No battery detected Green blinking: Charging Green steady on: Charge complete Red blinking: Error - shorted terminals, invalid pack chemistry |
| Connectors | Input: 2.5mm Center Positive |
| Color | Black |
| Finish | Case Material: ABS G1SM |
| Size | Charger: 174mm (6.85in) x 124mm (4.88in) x 54mm (2.12in) Charger Cable: 60.9cm (24in) |
| Weight | 460g (16.2oz) |
| Operating Temperature | 0°C to 45°C |
| Storage Temperature | -25°C to 70°C |
| Accessories Included | Power Supply - PS2524 Input Voltage: 100-240VAC, 47-63Hz Output Voltage: 24VDC Input Connector: IEC-320 Output Cable: 18Awg, 1.83m (6ft) Weight: 300g (10.5oz) Line Cord - UL/CSA 3 prong (North America), length 1.83m (6ft) |
| Accessories Optional | CA0003 - Vehicle Power Adapter Line Cords: USA: 1090-01-0002 AUS: 1090-01-0004 EUR: 1090-01-0008 |