

BP-2

RRT Inc Two-bay Battery Pack (BP-2) (12 or 24 VDC)

The RRT Inc Two-bay Battery Pack (BP-2) (12 or 24 VDC) is a state-of-the-art xx90 lithium battery power pack. It performs as a DC power-out power unit and can be alternatively loaded with either primary or secondary batteries (i.e. BA-5390, UBI-2590 battery ⁽¹⁾) The BP-2 can be customer ordered as either a 12 or 24 VDC (nominal) output version. The unit is circuit breaker protected (resettable) and will trip at 10 (12VDC) or 5 (24VDC) Amps. The BP-2 is housed entirely within an 5052 aluminum alloy case providing high strength, durability and excellent corrosion resistance, particularly in extreme temperature and harsh weather environments. Output power is transferred through a printed circuit board with installed diode protection ensuring that batteries discharge at a close to constant rate and reverse voltage charge to the installed batteries is avoided. Output power cables are customer defined and sold separately. Many output cable designs and configurations are possible depending customer equipment requirements (i.e. attending connection type, cable length requirements, etc.).



TECHNICAL DATA	
Battery Types Used:	*Primary or Secondary XX90 (see text ¹)
DC output:	Max 10 Amps @ 16.5VDC (12VDC version); Max 5 Amps @ 33VDC (24VDC version)
LED Indicators:	Red – Low voltage
Size:	14 3/4”L x 3”W x 7 1/8”H
Total Weight (ex battery):	4.6 lbs.
Operating Temperature:	Based on battery specification
Storage Temperature:	Based on battery specification. RRT does not advise using unit for long-term battery storage.

RRT Part Number 02-778-0046

Radio Reconnaissance Technologies, Inc.
 3328 Bourbon Street
 Fredericksburg, VA 22408
 Phone: 540-752-7448
 Fax: 540-752-7449
 RRT Inc. is ISO 9001:2015 certified