

**HTPU-1®**

**HARDENED TACTICAL  
POWER UNIT—ONE**

The Hardened Tactical Power Unit–One (HTPU®–1) is a self contained, water resistant, power unit capable of holding a single BA5390/UBI2590/BA5590/BB390 type battery. The HTPU®–1 is circuit/fuse protected and can be used to provide DC power to any type of electronic equipment. The HTPU®–1 is contained in a glass-filled polycarbonate case for strength and durability and has been specifically designed for use in austere weather conditions and adverse tactical environments. An automatic pressure release valve is located on the unit to allow for safe air travel and out-gases from the installed battery during operations. HTPU®–1 output power is transferred through installed diode protection which ensures that the battery discharges at a constant rate and the battery can not receive a charge from another power source.



TECHNICAL DATA	
<b>Outputs:</b>	Two Fused Outputs (Customer to specify either 12 or 24 VDC nonregulated)
<b>Indicators:</b>	Low Battery Voltage LED
<b>Cable Length:</b>	Normally 36", can be customer defined
<b>Dimensions:</b>	3"L x 7"W x 7"H
<b>Weight (W/Out Battery):</b>	1.4 lbs
<b>Power Out: (Nominal):</b>	Ultralife BA-5390 A/U +/- 11 Amp/hr @ 12 VDC Ultralife UBI-2590 +/- 14.4 Amp/hr @12 VDC Units can be "Daisy-Chained" for extended use

**Radio Reconnaissance Technologies, Inc.**  
3328 Bourbon Street  
Fredericksburg, VA 22408  
Phone: 540-752-7448  
Fax: 540-752-7449  
RRT Inc. is ISO 9001:2015 certified

**RRT Part Number 02-778-0039**  
Available under our GSA Schedule GS-35F-0575M